

> STAFFATRICI

> STIRRUP MACHINE



Specifiche | Specifications | Specificaciones | Spezifikationen | Especificações | Caractéristiques

ST16 EVO

								R=65 kg/mm ²				
77 x 61 h.100 cm	196 kg	5-	2 Hp 1,5 kW	1-phase version 220V / 50Hz with inverter 3-phase version 400V / 50Hz	21/min.	105 x 75 x h. 60 cm 216 kg 0.63 m ³		10	20	30	40	50
							mm	18	12	10	8	6
							in	0.71	0.47	0.39	0.31	0.24



Sede Legale: Via V. Alfieri, 43 - 35010 Gazzo (PD) - Italy
 Telefono +39 049 9425577 Fax +39 049 9425707
 e-mail: info@villaltasrl.it https://www.villaltasrl.it



GIU_2025



CESOIE COMBIMATE PIEGAFERRO



> CESCOIE > CUTTING MACHINE



Specifiche | Specifications | Specificaciones | Spezifikationen | Especificações | Caractéristiques

C34 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
82 x 50 h. 68 cm	235 kg	SAE 220 1,5 kg	3 Hp 2,2 kW	1-phase version 220V / 50Hz 3-phase version 400V / 50Hz	46/min.	120 x 80 x h. 80 cm 255 kg 0,57 m ³	10	20	30	10	20	30	
							28	20	16	26	18	14	
							in	1.10	0.79	0.63	1.02	0.71	0.55

C38 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
85 x 55 h. 72 cm	245 kg	SAE 220 1,5 kg	4 Hp 3 kW	1-phase version 220V / 50Hz 3-phase version 400V / 50Hz	52/min.	105 x 75 x h. 77 cm 260 kg 0,61 m ³	10	20	30	10	20	30	
							30	22	18	28	20	16	
							in	1.18	0.87	0.71	1.10	0.79	0.63

C44 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
98 x 56 h. 77 cm	405 kg	SAE 220 2 kg	4 Hp 3 kW	1-phase version 220V / 50Hz 3-phase version 400V / 50Hz	40/min.	105 x 75 x h. 90 cm 428 kg 0,65 m ³	10	20	30	10	20	30	
							34	28	22	32	22	18	
							in	1.34	1.10	0.87	1.26	0.87	0.71

C54 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
117 x 65 h. 87 cm	630 kg	SAE 220 3 kg	5,5 Hp 4 kW	400V / 50Hz	37/min.	117 x 75 x h. 92 cm 645 kg 0,81 m ³	10	20	30	10	20	30	
							46	32	24	40	30	22	
							in	1.81	1.26	0.94	1.57	1.18	0.87

C56 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
117 x 65 h. 92 cm	640 kg	SAE 220 3 kg	7,5 Hp 5,5 kW	400V / 50Hz	37/min.	117 x 75 x h. 97 cm 655 kg 0,85 m ³	10	20	30	10	20	30	
							48	34	26	42	32	24	
							in	1.89	1.34	1.02	1.65	1.26	0.94

C74 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
152 x 85 h. 110 cm	1.280	SAE 220 8 kg	10 Hp 7,5 kW	400V / 50Hz	30/min.	152 x 85 x h. 115 cm 1.330 kg 1,49 m ³	10	20	30	10	20	30	
							64	44	36	54	36	30	
							in	2.52	1.73	1.42	2.13	1.42	1.18



> COMBIMATE > COMBINED MACHINE



Specifiche | Specifications | Specificaciones | Spezifikationen | Especificações | Caractéristiques

TP25/32 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
80 x 100 h. 83 cm	342 kg	SAE 40 6 kg	3 Hp 2,2 kW	1-phase version 220V / 50Hz 3-phase version 400V / 50Hz	6/min.	75 x 105 x h. 100 cm 360 kg 0,79 m ³	10	20	30	10	20	30	
							24/28	18/20	14/16	22/26	16/18	12/14	
							in	0.94/1.10	0.70/0.79	0.55/0.63	0.87/1.02	0.63/0.71	0.47/0.55

TP32/36 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
90 x 107 h. 85 cm	400 kg	SAE 40 8 kg	3 Hp 2,2 kW	3-phase version 400V / 50Hz	8/min.	90 x 107 x h. 100 cm 420 kg 0,96 m ³	10	20	30	10	20	30	
							28/34	20/24	16/20	32	24	18	
							in	1.10/1.34	0.79/0.94	0.63/0.79	1.26	0.94	0.71

TP40/46 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
150 x 120 h. 90 cm	620 kg	SAE 40 14 kg	5,5 Hp 4 kW	400V / 50Hz	6/min.	105 x 120 x h. 105 cm 635 kg 1,32 m ³	10	20	30	10	20	30	
							32/38	22/28	18/22	36	28	22	
							in	1.26/1.50	1.26/1.50	0.71/0.87	1.18/1.42	0.79/0.98	0.63/0.79



> PIEGA FERRO > BENDING MACHINE



Specifiche | Specifications | Specificaciones | Spezifikationen | Especificações | Caractéristiques

P34 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
75 x 80 h. 85 cm	285 kg	SAE 40 5 kg	3 Hp 2,2 kW	1-phase version 220V / 50Hz 3-phase version 400V / 50Hz	11/min.	75 x 80 x h. 100 cm 300 kg 0,60 m ³	10	20	30	10	20	30	
							30	22	18	28	20	16	
							in	1.18	0.87	0.71	1.10	0.79	0.63

P38 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
86 x 90 h. 85 cm	365 kg	SAE 40 8 kg	4 Hp 3 kW	1-phase version with inverter 3 Kw 3-phase version 400V / 50Hz	9/min.	86 x 90 x h. 100 cm 380 kg 0,77 m ³	10	20	30	10	20	30	
							34	26	20	32	24	18	
							in	1.34	1.02	0.79	1.26	0.94	0.71

P44 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
105 x 95 h. 89 cm	485 kg	SAE 40 13 kg	4 Hp 3 kW	1-phase version with inverter 3 Kw 3-phase version 400V / 50Hz	6/min.	120 x 95 x h. 104 cm 509 kg 1,04 m ³	10	20	30	10	20	30	
							38	30	24	36	28	22	
							in	1.50	1.18	0.94	1.42	1.10	0.87

P54 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
105 x 95 h. 89 cm	585 kg	SAE 40 13 kg	5,5 Hp 4 kW	3-phase version 400V / 50Hz	6/min.	105 x 95 x h. 104 cm 600 kg 1,04 m ³	10	20	30	10	20	30	
							44	34	28	40	32	24	
							in	1.73	1.34	1.10	1.57	1.26	0.94

P56 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
130 x 95 h. 89 cm	710 kg	SAE 40 13 kg	7,5 Hp 5,5 kW	3-phase version 400V / 50Hz	5/min.	130 x 95 x h. 104 cm 725 kg 1,28 m ³	10	20	30	10	20	30	
							44	34	28	40	32	24	
							in	1.73	1.34	1.10	1.57	1.26	0.94

P74 EVO													
Dimensions	Weight	SAE	Power	Voltage	Speed	Capacity	R=65 kg/mm ²			R=85 kg/mm ²			
							mm	mm	mm	mm	mm	mm	
160 x 116 h. 96 cm	1.600 kg	SAE 40 25 kg	10 Hp 7,5 kW	400V / 50Hz	5/min.	160 x 116 x h. 111 cm 1.650 kg 2,06 m ³	10	20	30	10	20	30	
							60	42	34	50	36	30	
							in	2.36	1.65	1.34	1.97	1.42	1.18

